DRUMMOND™
A LAWSON BRAND

Safety Data Sheet

Issue date 06-Jun-2018 **Revision date** 03-Jan-2020 **Revision Number** 3

1. IDENTIFICATION

Product identification

Product identifier	Drummond™ Scandal Swipes Graffiti Remover Wipes
Other means of identification	DN4740
Recommended use	Cleaner
Restrictions on use	Cleaning wipes

Supplier

Corporate Headquarters:
Drummond™, A Lawson Brand
Lawson Products, Inc.
8870 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website https://www.lawsonproducts.com

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Symbol

Signal word DANGER

Hazard statements
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H225 - Highly flammable liquid and vapor

Precautionary statements

Prevention

P264 - Wash face, hands and any exposed skin thoroughly after handling
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P280 - Wear protective gloves/protective clothing and eye/face protection
P235 - Keep cool

Response

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

Skin

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell

Fire

P370 + P378 - IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish

Storage

P405 - Store locked up
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Hazard(s) Not Otherwise Classified (HNOC)

Harmful to aquatic life with long lasting effects.

Physical Hazards Not Otherwise Classified (PHNOC)

None known.

Unknown acute toxicity

0%.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition

Mixture.

Chemical name	CAS-No	Weight %
Dimethyl Glutarate	1119-40-0	10-20
Propylene glycol monomethyl ether	107-98-2	10-20
Tripropylene Glycol Methyl Ether	25498-49-1	10-20
Acetone	67-64-1	1-10
2-Butoxyethanol	111-76-2	1-10
1-Butanol, 2-methyl-, acetate	624-41-9	1-3
Dimethyl Succinate	106-65-0	1-3
n-Amyl acetate	628-63-7	1-3

The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST-AID MEASURES

Necessary first-aid measures

General Information	Take off contaminated clothing and shoes immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before re-use.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion	Not an expected route of exposure. Call a physician or Poison Control Center immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
Skin contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. In the case of skin irritation or allergic reaction see a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Most important symptoms (acute)	May cause drowsiness or dizziness. Headache. Nausea or vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Most important symptoms (over-exposure)	Not available.
Indication of any immediate medical attention and special treatment needed	Thermal burns: flush with water immediately. While flushing, remove clothes which do not adhere to the affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Dry Chemical, Carbon Dioxide, Foam or Water Fog. Fire may float as if an oil fire.
Unsuitable extinguishing media	Full water jet.
Specific hazards	Vapors may form explosive mixture with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. During fire, gases hazardous to health may be formed.
Special protective equipment for fire-fighters	Use water spray to keep fire-exposed containers cool. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protection recommended in Section 8. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent entry into waterways, sewers, basements, and confined areas. Avoid release to the environment. See Section 12: Ecological Information. Dispose of contents/container to an approved waste disposal plant.
Methods and materials for containment and cleaning up	Prevent further leakage or spillage if safe to do so. Small Spill:. Wipe up with absorbent material (e.g. cloth, fleece). Large Spill:. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

7. HANDLING AND STORAGE

Precautions for safe handling	Avoid contact with eyes, skin, and clothing. Do not smoke while using. Use only with adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Keep away from open flames, hot surfaces and sources of ignition. Use only in an area containing flame proof equipment.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, and well-ventilated place. Keep out of reach of children. Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, beverages, and feed. Incompatible with strong acids, alkalis, or oxidizing agents. alkali metal hydroxides.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Dimethyl Glutarate	-	-	-
Propylene glycol monomethyl ether	-	100 ppm STEL 50 ppm TWA	150 ppm STEL 540 mg/m³ STEL 100 ppm TWA 360 mg/m³ TWA
Tripropylene Glycol Methyl Ether	-	-	-
Acetone	1000 ppm TWA 2400 mg/m³ TWA	500 ppm STEL 250 ppm TWA	250 ppm TWA 590 mg/m³ TWA
2-Butoxyethanol	Skin 50 ppm TWA 240 mg/m³ TWA	20 ppm TWA	5 ppm TWA 24 mg/m³ TWA
1-Butanol, 2-methyl-, acetate	-	100 ppm STEL 50 ppm TWA	-
Dimethyl Succinate	-	-	-
n-Amyl acetate	100 ppm TWA 525 mg/m³ TWA	100 ppm STEL 50 ppm TWA	100 ppm TWA 525 mg/m³ TWA

Appropriate engineering controls

Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye protection

Safety glasses with side-shields.

Skin and body protection

Impervious gloves.

Respiratory protection

None required. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respirator is recommended.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Dimethyl Glutarate	-	-	-	-	-	-	-	-	-	-
Propylene glycol monomethyl ether	150 ppm STEL 553 mg/m³ STEL 100 ppm TWA 369 mg/m³ TWA	100ppmSTEL 50ppmTWA	50 ppm TWA 100 ppm STEL	150 ppm STEL 553 mg/m³ STEL 100 ppm TWA 369 mg/m³ TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	150 ppm STEV 553 mg/m³ STEV 100 ppm TWAEV 369 mg/m³ TWAEV	150 ppm STEL 100 ppm TWA
Tripropylene Glycol	-	-	-	-	-	-	-	-	-	-

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Methyl Ether										
Acetone	750 ppm STEL 1800 mg/m³ STEL 500 ppm TWA 1200 mg/m³ TWA	500ppmSTEL 250ppmTWA	250 ppm TWA 500 ppm STEL	750 ppm STEL 1782 mg/m³ STEL 500 ppm TWA 1188 mg/m³ TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	1000 ppm STEV 2380 mg/m³ STEV 500 ppm TWAEV 1190 mg/m³ TWAEV	750 ppm STEL 500 ppm TWA
2-Butoxyethanol	20 ppm TWA 97 mg/m³ TWA	20ppmTWA	20 ppm TWA	25 ppm TWA 121 mg/m³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV 97 mg/m³ TWAEV	30 ppm STEL 20 ppm TWA
1-Butanol, 2-methyl-, acetate	-	100ppmSTEL 50ppmTWA	50 ppm TWA 100 ppm STEL	-	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEV 532 mg/m³ STEV 50 ppm TWAEV 266 mg/m³ TWAEV	100 ppm STEL 50 ppm TWA
Dimethyl Succinate	-	-	-	-	-	-	-	-	-	-
n-Amyl acetate	100 ppm STEL 532 mg/m³ STEL 50 ppm TWA 266 mg/m³ TWA	100ppmSTEL 50ppmTWA	50 ppm TWA 100 ppm STEL	100 ppm TWA 532 mg/m³ TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEL 50 ppm TWA	100 ppm STEV 532 mg/m³ STEV 50 ppm TWAEV 266 mg/m³ TWAEV	100 ppm STEL 50 ppm TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid

Color Colorless

Odor plumeria

Odor threshold Not available

pH 6.3

Melting point/range °C Not available

Melting point/range °F Not available

Boiling point/range °C 100 °C

Boiling point/range °F 212 °F

Flash point °C 16.67

Flash point °F 62

Flash point method used Not available

Evaporation rate No data available

Flammability (Solid, Gas) Not available

Lower explosion limit	Not available
Upper explosion limit	Not available
Vapor pressure	No data available
Vapor density	>1 (Air = 1)
Relative density	0.98 - 0.97
Solubility	Miscible with water
Partition coefficient (n-octanol/water)	Not applicable
Autoignition temperature °C	Not applicable
Autoignition temperature °F	Not applicable
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Avoid heat, sparks, and other sources of ignition. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Inhalation. Eyes. Dermal.
Symptoms	May be harmful if inhaled. May cause eye irritation. May cause eye irritation including redness, tearing, itching, and swollen eyes. May cause skin irritation. Ingestion not an expected route of entry.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Not available.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Dimethyl Glutarate	> 5.6 mg/L (Rat) 4 h	> 5000 mg/kg (Rabbit)	> 5000 mg/kg (Rat)
Propylene glycol monomethyl ether	> 7559 ppm (Rat) 6 h	= 13 g/kg (Rabbit)	= 5000 mg/kg (Rat)
Tripropylene Glycol Methyl Ether	-	= 15440 mg/kg (Rabbit)	= 3200 mg/kg (Rat)
Acetone	= 50100 mg/m³ (Rat) 8 h	> 15700 mg/kg (Rabbit)	= 5800 mg/kg (Rat)
2-Butoxyethanol	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h	= 99 mg/kg (Rabbit)	= 470 mg/kg (Rat)
1-Butanol, 2-methyl-, acetate	-	-	-
Dimethyl Succinate	-	> 5 g/kg (Rabbit)	> 5 g/kg (Rat)
n-Amyl acetate	-	-	= 6500 mg/kg (Rat) > 1600 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Dimethyl Glutarate	-	-	-	-
Propylene glycol monomethyl ether	A4	-	-	-
Tripropylene Glycol Methyl Ether	-	-	-	-
Acetone	A4	-	-	-
2-Butoxyethanol	A3	Group 3	-	-
1-Butanol, 2-methyl-, acetate	-	-	-	-
Dimethyl Succinate	-	-	-	-
n-Amyl acetate	-	-	-	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Dimethyl Glutarate	-	-	-	-	-	-
Propylene glycol monomethyl ether	-	-	ACGIH A4	-	ACGIH A4	-
Tripropylene Glycol Methyl Ether	-	-	-	-	-	-
Acetone	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
2-Butoxyethanol	-	-	ACGIH A3	-	ACGIH A3	-
1-Butanol, 2-methyl-, acetate	-	-	-	-	-	-
Dimethyl Succinate	-	-	-	-	-	-
n-Amyl acetate	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life with long lasting effects

Chemical name	Algae/aquatic plants	Fish
Dimethyl Glutarate	-	19.6 - 26.2: 96 h Pimephales promelas mg/L LC50 static
Propylene glycol monomethyl ether	-	20.8: 96 h Pimephales promelas g/L LC50 static 4600 - 10000: 96 h Leuciscus idus mg/L LC50 static
Tripropylene Glycol Methyl Ether	-	11619: 96 h Pimephales promelas mg/L LC50 static
Acetone	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50
2-Butoxyethanol	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50
1-Butanol, 2-methyl-, acetate	-	-
Dimethyl Succinate	-	50 - 100: 96 h Brachydanio rerio mg/L LC50 static
n-Amyl acetate	-	650: 96 h Lepomis macrochirus mg/L LC50 static

Persistence and degradability Not available.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Dimethyl Glutarate 1119-40-0	1119-40-0	-
Propylene glycol monomethyl ether 107-98-2	107-98-2	-0.437
Tripropylene Glycol Methyl Ether 25498-49-1	25498-49-1	-
Acetone 67-64-1	67-64-1	-0.24
2-Butoxyethanol 111-76-2	111-76-2	0.81 25 °C
1-Butanol, 2-methyl-, acetate 624-41-9	624-41-9	-
Dimethyl Succinate 106-65-0	106-65-0	0.19 25 °C
n-Amyl acetate 628-63-7	628-63-7	-

Mobility in soil Not available.

Other adverse effects Not available

13. DISPOSAL CONSIDERATIONS

Disposal information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate closed container. Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No	UN1993
Proper shipping name	Flammable Liquid, n.o.s. (Acetone)
Hazard Class(es)	3
Packing group	II
Special Provisions	LTD QTY

TDG

ID-No	UN1993
Proper shipping name	Flammable Liquid, n.o.s. (Acetone)
Hazard Class(es)	3
Packing group	II
Special Provisions	LTD QTY

IATA

ID-No	UN1993
Proper shipping name	Flammable Liquid, n.o.s. (Acetone)
Hazard Class(es)	3
Subsidiary Risk	
Packing group	II

IMDG/IMO

ID-No	UN1993
Proper shipping name	Flammable Liquid, n.o.s. (Acetone)
Hazard Class(es)	3
Packing group	II

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Dimethyl Glutarate	1119-40-0	-	-	-
Propylene glycol monomethyl ether	107-98-2	-	-	-
Tripropylene Glycol Methyl Ether	25498-49-1	-	-	-
Acetone	67-64-1	-	-	-
2-Butoxyethanol	111-76-2	-	-	-
1-Butanol, 2-methyl-, acetate	624-41-9	-	-	-
Dimethyl Succinate	106-65-0	-	-	-
n-Amyl acetate	628-63-7	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Dimethyl Glutarate	1119-40-0	-	-	-
Propylene glycol monomethyl ether	107-98-2	X	X	X
Tripropylene Glycol Methyl Ether	25498-49-1	-	X	X
Acetone	67-64-1	X	X	X
2-Butoxyethanol	111-76-2	X	X	X
1-Butanol, 2-methyl-, acetate	624-41-9	-	-	-
Dimethyl Succinate	106-65-0	-	-	-
n-Amyl acetate	628-63-7	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Dimethyl Glutarate	1119-40-0	-
Propylene glycol monomethyl ether	107-98-2	-
Tripropylene Glycol Methyl Ether	25498-49-1	-
Acetone	67-64-1	-
2-Butoxyethanol	111-76-2	-
1-Butanol, 2-methyl-, acetate	624-41-9	-
Dimethyl Succinate	106-65-0	-
n-Amyl acetate	628-63-7	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Dimethyl Glutarate	1119-40-0	-	-
Propylene glycol monomethyl ether	107-98-2	-	-
Tripropylene Glycol Methyl Ether	25498-49-1	-	1.0 %
Acetone	67-64-1	5000 lb 2270 kg	-
2-Butoxyethanol	111-76-2	-	1.0 %
1-Butanol, 2-methyl-, acetate	624-41-9	-	-
Dimethyl Succinate	106-65-0	-	-
n-Amyl acetate	628-63-7	5000 lb 2270 kg	-

US EPA SARA 311/312 hazardous categorization Acute Health Hazard
Fire Hazard

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Dimethyl Glutarate	X	X	-
Propylene glycol monomethyl ether	X	X	-
Tripropylene Glycol Methyl Ether	X	X	-
Acetone	X	X	-

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
2-Butoxyethanol	X	X	-
1-Butanol, 2-methyl-, acetate	X	X	-
Dimethyl Succinate	X	X	-
n-Amyl acetate	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health	Not available
Flammability	Not available
Instability	Not available

HMIS

Health	Not available
Flammability	Not available
Physical hazards	Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 06-Jun-2018

Revision date 03-Jan-2020

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Orgnaization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet