



ISO-9001 Registered Quality System.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA**LUBRIPLATE No.'s 130-A & 130-AA****DESCRIPTION**

LUBRIPLATE No's. 130-A & 130-AA are designed for those applications where a grease-type lubricant possessing extremely good water repellency and superior lubrication characteristics are desired.

APPLICATIONS

These products are recommended for:

- ⇒ Plain bearings
- ⇒ Cams
- ⇒ Guides
- ⇒ Open gears
- ⇒ Slides and chassis lubrication
- ⇒ Where temperatures do not exceed 170°F

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- ⇒ Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*	
		No. 130-A	No. 130-AA
Type of Base		Calcium	Calcium
Worked Penetration	ASTM D-217	220/265	310/340
NLGI No.		2 / 3	1
ASTM Melting Point	ASTM D-87	200°F/93°C	190°F/88°C
Mineral Oil Viscosity:			
SUS @ 100°F	ASTM D-2161	750	750
cSt @ 40°C	ASTM D-445	135	135
Color	Visual	Beige	Beige
Character		Smooth	Smooth

PACKAGING AVAILABLE

Carton, 12/16 oz. Plastic Tubs

Carton, 4/6 lb. Plastic Tubs

35 lb. Pail

120 lb. Quarter Size Drum

420 lb. Full Size Drum

Carton, 36/1¼ oz. Tubes (1X6)

Carton, 36/10 oz. Plastic Tubes

No. 130-A

L0043-004

L0043-005

L0043-035

L0043-040

No. 130-AA

L0044-004

L0044-005

L0044-035

L0044-039

L0044-040

L0044-086

L0044-092

