Safety Data Sheet VOLTZ AEROSOL

Supercedes Date 02/14/2014

Issuing Date 07/10/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name VOLTZ AEROSOL Recommended use Solvent Information on Manufacturer CHEMSEARCH DIV. OF NCH CORP.

BOX 152170 **IRVING, TX 75015**

Product Code 5491 Chemical nature Solvent mixture **Emergency Telephone Number** CHEMTREC® 800-424-9300 Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Color Colorless - Light yellow Physical state liquid **Odor** Orange

Category 1

Compressed Gas

Category 1

Category 3 Category 2

Category 2B

Category 1

Category 3

Category 2

GHS

Classification

Physical Hazards

Flammable Aerosols Gases under pressure

Health Hazard

Aspiration Toxicity

Acute Inhalation Toxicity - Gas

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin sensitization

Specific target organ systemic toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

Other hazards

None

Labeling Signal Word

DANGER



Hazard statements

H222 - Extremely flammable aerosol

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H320 - Causes eye irritation

H304 - May be fatal if swallowed and enters airways

H373 - May cause damage to organs through prolonged or repeated exposure

H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P270 - Do not eat, drink or smoke when using this product.

P260 - Do not breathe vapor, mist or gas

P271 - Use in a well-ventilated area.

P285 - In case of inadequate ventilation wear respiratory protection

P280 - Wear protective gloves, protective clothing and eye protection. P264 - Wash face, hands and any exposed skin thoroughly after handling

P272 - Contaminated work clothing should not be allowed out of the workplace

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P342 + P311 - If experiencing respiratory symptoms, call a physician

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P333 + P313 - If skin irritation or rash occurs, get medical attention

P362 - Take off contaminated clothing and wash before reuse

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists, get medical attention.

P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents and container in accordance with applicable local

regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	64741-66-8	40-70
D-Limonene	5989-27-5	15-40
Propane	74-98-6	10-30
Butane	106-97-8	1-5

4. FIRST AID MEASURES

General advice Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation

develops and persists.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation

develops and persists. Remove contaminated clothing and shoes. Wash contaminated clothing

before re-use.

Inhalation Move to fresh air. In case of shortness of breath, give oxygen. If breathing has stopped, apply artificial

respiration. Get medical attention immediately.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never

give anything by mouth to an unconscious person.

Notes to physician Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and

enters airways. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Flash Point 39 °F / 4 °C Method Seta closed cup

Flammability Limits in Air %: Solvent mixture. Upper: 9.5 Lower: 0.7

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Dry chemical.

Specific hazards arising from the chemical

Flame extension: >30 inches / >76 cm and Burnback: 5 inch / 13 cm. Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NOHSC (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) -

NFPA Health 2 Flammability 4 Instability 0
HMIS Health 2 Flammability 4 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Prevent further leakage or spillage if safe to do so. Use personal protective equipment. Material can

create slippery conditions. Remove all sources of ignition. Ensure adequate ventilation.

Environmental PrecautionsDo not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

Neutralizing Agent Not applicable.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and

clothing.

Storage Keep away from heat and sources of ignition. Keep containers tightly closed in a dry, cool and well-

ventilated place.

Storage TemperatureMinimum35 °F / 2 °CMaximum120 °F / 49 °CStorage ConditionsIndoorXOutdoorHeatedRefrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Propane	TWA: 1000 ppm	TWA: 1000 ppm	2100 ppm
		TWA: 1800 mg/m ³	TWA: 1000 ppm
		3	TWA: 1800 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm
			TWA: 1900 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should

be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Wear suitable protective clothing, Impervious gloves.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Ensure that eyewash stations and safety showers are close to the workstation location. Remove

and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state liquid Viscosity Non viscous . Colorless - Light yellow Color Odor Orange **Odor Threshold** Not applicable **Appearance** Transparent Not applicable **Specific Gravity** 0.704 рΗ **Evaporation Rate** Percent Volatile (Volume) 37.4 0 VOC Content (%) 100 VOC Content (g/L) 0 **Vapor Pressure** 1965 mmHg @ 70°F Vapor Density 1.7

Solubility n-Octanol/Water Partition Negligible No data available Melting Point/Range No data available **Decomposition Temperature** No data available **Boiling Point/Range** 340 °F / 171 °C Flammability (solid, gas) No data available Flash Point 39 °F / 4 °C Method Seta closed cup

Autoignition Temperature No information available.

Flammability Limits in Air %: Solvent mixture Upper: 9.5 Lower: 0.7

10. STABILITY AND REACTIVITY

Chemical Stability Stable. Hazardous polymerization does not occur.

Conditions to Avoid Keep away from open flames, hot surfaces, and sources of ignition. **Incompatible Products** Strong oxidizing agents, Acids, Vinyl compounds, Halogenated

hydrocarbon. **Decomposition Temperature** No data available **Hazardous Decomposition Products** Carbon oxides.

Possibility of Hazardous Reactions None under normal processing.

11. TOXICOLOGICAL INFORMATION

No information available. **Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 5,990.39 **Dermal LD50** 2.000.00

Inhalation LC50

Gas No information available

Mist 6.28 Vapor 6.28

Principle Route of Exposure Skin contact, Eye contact, Inhalation.

Primary Routes of Entry Inhalation, Skin Absorption.

Acute Effects:

Chronic Toxicity

Eyes Causes eye irritation.

Skin Causes skin irritation. May cause allergic skin reaction. May be absorbed through the skin in harmful

Inhalation May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May

cause central nervous system depression. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness. May cause

allergic respiratory reaction.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if Ingestion

> swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways. Repeated and prolonged exposure to solvents may cause brain and nervous system damage. May

cause sensitization by skin contact. May cause sensitization by inhalation. Liver and kidney injuries

may occur.

Target Organ Effects Aggravated Medical Conditions Central nervous system, Liver, Kidney, Heart, Immune system.

Respiratory disorders, Skin disorders, Neurological disorders, Liver disorders, Kidney

disorders, Heart disease.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h	no data available	no data available
D-Limonene	= 4400 mg/kg (Rat)	> 5 g/kg (Rabbit)	no data available	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m ³ (Rat) 4 h	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental	Reproductive Toxicity	Target Organ Effects
			Toxicity		
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	no data available	no data available	no data available	no data available	CNS
D-Limonene	no data available	Skin sensitization, Respiratory sensitization	no data available	no data available	CNS, immune system, lungs, liver, kidneys, respiratory system
Propane	no data available	no data available	no data available	no data available	CNS, heart
Butane	no data available	no data available	no data available	no data available	CNS, heart

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
D-Limonene	not applicable	Group 3	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information

Component Information

No information available.

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
Naphtha (petroleum)light alkylate (<3% DMSO extractable)	EC50 = 30000 mg/L Pseudokirchneriella	No information available.	No information available	2: 48 h Mysidopsis bahia mg/L LC50	N/A
,	subcapitata 72 h			, and the second	
D-Limonene	No information available.	LC50 0.619 - 0.796 mg/L Pimephales	No information available	No information available.	N/A
		promelas 96 h			
		LC50 = 35 mg/L Oncorhynchus			
		mykiss 96 h			
Propane	No information available.	No information available.	No information available	No information available.	2.3
Butane	No information available.	No information available.	No information available	No information available.	2.89

Persistence and Degradability

Bioaccumulation Mobility

No information available. No information available. No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations. **Container Disposal**

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be

taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT DOT

Proper Shipping Name Consumer commodity

Hazard Class ORM-D

Description Consumer commodity, ORM-D,

TDG

Proper shipping name Aerosols **Hazard Class** 2.1 **UN-No** UN1950

AEROSOLS,2.1,UN1950 LTD QTY Description

ICAO

UN1950 UN-No

Proper Shipping Name Aerosols
Hazard Class 2.1

Shipping Description Aerosols, UN1950 LTD QTY

IATA

UN-No UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 Precautionary Statements - 10L

Response

Shipping Description UN1950, Aerosols, flammable, 2.1 LTD QTY

IMDG/IMO

Proper Shipping Name Aerosols
Hazard Class 2.1
UN-No UN1950
EmS No. F-D, S-U

Description UN1950, Aerosols, 2.1 LTD QTY

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

16. OTHER INFORMATION

Prepared By Angela Hutson Supercedes Date 02/14/2014 Issuing Date 07/10/2015

Reason for RevisionNo information available.GlossaryNo information available.List of References.No information available.

CHEMSEARCH DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.