

#120 LUST



### Material Safety Data Sheet

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Photo Mount Spray Adhesive 6090, 6094  
**MANUFACTURER:** 3M  
**DIVISION:** Stationery Products  
**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 10/20/10  
**Supersedes Date:** 10/19/10

**Document Group:** 26-3876-5

**Product Use:**  
Intended Use: Adhesive

## SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
ACETONE	67-64-1	30 - 40
PROPANE	74-98-6	22 - 33
CYCLOHEXANE	110-82-7	15 - 25
NON-HAZARDOUS COMPONENTS - N.J.T.S. REGISTRY NUMBER 04499600-6726	Trade Secret	8 - 20
WATER	7732-18-5	1 - 3
DIMETHYL GLUTARATE	1119-40-0	0.5 - 2

## SECTION 3: HAZARDS IDENTIFICATION

### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** Light yellow-gold with solvent odor.  
**General Physical Form:** Liquid  
**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and

flash back. May cause severe eye irritation. May cause target organ effects.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Skin Contact:**

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Inhalation:**

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. Get immediate medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

#### 4.2 NOTE TO PHYSICIANS

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

### SECTION 5: FIRE FIGHTING MEASURES

#### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	<=-100 °F [Test Method: Closed Cup]
Flammable Limits - LEL	1.6 %
Flammable Limits - UEL	8.4 %

#### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available.

#### Environmental procedures

Place in a metal container approved for transportation by appropriate authorities.

#### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill.

Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. No smoking while handling this material. Do not spray near flames or sources of ignition. Avoid breathing of vapors, mists or spray. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Provide appropriate local exhaust ventilation on open containers. Do not use in a confined area or areas with little or no air movement. Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges

Half facepiece or fullface supplied-air respirator

Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
CYANIDES	OSHA	TWA, as CN	5 mg/m3	Skin Notation*
CYCLOHEXANE	ACGIH	TWA	100 ppm	
CYCLOHEXANE	OSHA	TWA	1050 mg/m3	
DIMETHYL GLUTARATE	CMRG	TWA, as Dimethyl Esters	1.5 ppm	
PROPANE	OSHA	TWA	1800 mg/m3	

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Odor, Color, Grade:</b>	Light yellow-gold with solvent odor.
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	<=-100 °F [ <i>Test Method: Closed Cup</i> ]
<b>Flammable Limits - LEL</b>	1.6 %
<b>Flammable Limits - UEL</b>	8.4 %
<b>Boiling point</b>	-40 °F
<b>Density</b>	0.7 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	4760 mmHg
<b>Specific Gravity</b>	0.7 [ <i>Ref Std: WATER=1</i> ]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Solubility in Water</b>	Negligible
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	0 % weight
<b>Volatile Organic Compounds</b>	49 %
<b>Kow - Oct/Water partition coef</b>	<i>No Data Available</i>
<b>Percent volatile</b>	85 %
<b>VOC Less H2O &amp; Exempt Solvents</b>	494 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Viscosity</b>	<i>No Data Available</i>

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:**

**10.1 Conditions to avoid**

Heat  
Sparks and/or flames

**10.2 Materials to avoid**

None known

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion

**SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

**SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION**

Not determined.

**CHEMICAL FATE INFORMATION**

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. Facility must be capable of handling aerosol cans. Dispose of empty product containers in a sanitary landfill.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

**SECTION 14: TRANSPORT INFORMATION**

**ID Number(s):**

70-0050-3203-5, 70-0050-3946-9, 70-0050-5653-9

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
CYCLOHEXANE	110-82-7	15 - 25

### STATE REGULATIONS

Contact 3M for more information.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

**NFPA Hazard Classification**

**Health: 2 Flammability: 4 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:**

Section 9: Property description for optional properties was modified.  
Copyright was modified.  
Section 6: Release measures information was deleted.  
Section 6: Release measures heading was deleted.  
Section 8: Eye/face protection information was modified.  
Section 8: Skin protection - recommended gloves information was modified.  
Section 8: Respiratory protection - recommended respirators information was modified.  
Section 10: Materials and conditions to avoid physical property was deleted.  
Section 14: Transportation legal text was modified.  
Section 1: Initial issue message was modified.  
Section 14: ID Number(s) Template 1 was modified.  
Section 8: Exposure guidelines ingredient information was modified.  
Section 8: Exposure guidelines legend was deleted.  
Section 6: Environmental procedures heading was added.  
Section 6: Personal precautions heading was added.  
Section 10.1 Conditions to avoid heading was added.  
Section 10.2 Materials to avoid heading was added.  
Section 6: Personal precautions information was added.  
Section 6: Environmental procedures information was added.  
Section 6: Methods for cleaning up information was added.  
Section 10: Materials to avoid physical property was added.  
Section 10: Conditions to avoid physical property was added.  
Section 6: Clean-up methods heading was added.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**